

## EMERGENCY EXIT



405 T, 405 K, 405 J



409 T, 409 K, 409 J



446 T, 446 K, 446 J



447 T, 447 K, 447 J



443 T, 443 K, 443 J



444 T, 444 K, 444 J



448 T, 448 K, 448 J



449 T, 449 K, 449 J



401 T, 401 K, 401 J



446T (Exit)

Double Sided



405 DST, 405 DSK, 405 DSJ

Double Sided



449 DST, 449 DSK, 449 DSJ

Double Sided



448 DST, 448 DSK, 448 DSJ

## ESCAPE ROUTE



4167 PT



4168 PT



4171 PT



4172 PT



4173 PT



4169 PT



4174 PT



4170 PT



4173PT (Escape Direction)

### Sizes:

DSJ: 200 x 450mm, DSK: 150 x 400mm,  
DST: 120 x 340mm, J: 200 x 450mm, K: 150 x 400mm,  
PT: 100 x 300mm, T: 120 x 340mm

Please order as required,  
state: (V) for Self Adhesive Vinyl or (R) for Rigid PVC.

ISO 17398 Safety colours & safety signs - Classification, performance & durability of safety signs

This International Standard specifies requirement for a performance related classification system for safety signs according to expected service environment, including photometric properties.

